



**Afilli**  
Housekeeping and Hobby

## Afilli Multisurface Acrylic Metallic

Afilli Multisurface Acrylic Metallic is a metallic texture and gloss, water-based paint developed to provide superior performance on all surfaces.



### THINNING

The product is ready-to-use. Recommended to be applied in minimum two coats according to the applied surface's condition and color used after thinning by maximum 5% by volume with clean water in brush, roller and sponge applications.

### DRYING TIME (@ 20°C, 65% RH):

Resting period between coats: 4 hours  
Final Dry: 24 hours Full Drying: 7 days (drying time may increase at higher relative humidity and lower temperature).

### CONSUMPTION

Depending on the type, absorbency and structure of the application surface, an area of 15-20 m<sup>2</sup> area can be painted in a single coat with 1 Liter. A controlled sample test should be performed prior to the final consumption.

### Airless Spraying

Pressure: 120-140 bars  
Nozzle angle: 50° Nozzle size (Inch): 0.019"  
Thinning: Ready to use. Recommended to be applied in one coat provided that the sufficient film thickness is achieved after thinning by 5% with clean water in airless spraying if needed.

### STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

### PACKAGING

250 ml  
120 ml

### FEATURES

Adheres strongly to all surfaces and holds on. Has high coverage. Can be used in interior and exterior spaces. Easy to apply. Does not leave brush or roller marks. Provides a smooth and very glossy texture. Stain resistant thanks to its strong wipe cleaning performance. Includes low VOC, harmless to health. Odorless. Compliant with EN 71-3 standards.

### APPLICATION SURFACES

Can be applied on surfaces such as wood, metal, glass, ceramic, plastic, stone, PVC, walls, cardboard and cloth.

### APPLICATION

Application surfaces should be clean. Should be cleaned from dirt and dust. Hardening and total clinging to surface is achieved in 7 days. One coat of white color Multisurface Acrylic Matt can be applied to the surface in advance to increase the adhesion and coverage of Multisurface Acrylic Metallic. For higher protection and resistance to physical conditions, Multisurface Varnish can be applied on painted surface.

### WARNING-1

Ensure that the ambient and surface temperatures are between +5°C and +30°C throughout the application and drying out period of the product.